### SHANGHAI HUATING CHEMICALS FACTORY CO.,LTD

# Material Safety Data Sheet Cuprous chloride MSDS

#### **Section 1: Chemical Product and Company Identification**

Product Name: Cuprous chloride Catalog Codes: SLC3931, SLC1138

CAS#: 7758-89-6 RTECS: GL6990000

TSCA: TSCA 8(b) inventory: Cuprous chloride

CI#: Not available.

Synonym: Copper(I) chloride Chemical Name: Not available. Chemical Formula: CuCl

**Contact Information:** 

Shanghai Huating Chemicals Factory Co.,Ltd

Rm 2306, No.382, Tacheng Rd, Jiading, Shanghai

Tel:+86-21-59522390 Fax:+86-21-69988155

Email:huatingchem@gmail.com

#### Section 2: Composition and Information on Ingredients

Composition:

Name CAS # % by Weight

Cuprous chloride 7758-89-6 100

Toxicological Data on Ingredients: Cuprous chloride: ORAL (LD50): Acute: 140 mg/kg [Rat].

#### **Section 3: Hazards Identification**

#### Potential Acute Health Effects:

Very hazardous in case of ingestion. Hazardous in case of eye contact (irritant), of inhalation. Slightly hazardous in case of skin contact (irritant). Corrosive to eyes and skin. The amount of tissue damage depends on length of contact. Eye contact can result in corneal damage or blindness. Skin contact can produce inflammation and blistering. Inhalation of dust will produce irritation to gastro-intestinal or respiratory tract, characterized by burning, sneezing and coughing. Severe over-exposure can produce lung damage, choking, unconsciousness or death.

Potential Chronic Health Effects:

Very hazardous in case of ingestion. Hazardous in case of eye contact (irritant), of inhalation. Slightly hazardous in case of skin contact (irritant). CARCINOGENIC EFFECTS: Not available. MUTAGENIC

### SHANGHAI HUATING CHEMICALS FACTORY CO.,LTD

EFFECTS: Not available. TERATOGENIC

EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to kidneys, lungs, liver, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated skin exposure can produce local skin destruction, or dermatitis. Repeated inhalation of dust can produce varying degree of respiratory irritation or lung damage. Repeated exposure to an highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

#### Section 4: First Aid Measures

#### Eye Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention. Skin Contact:

If the chemical got onto the clothed portion of the body, remove the contaminated clothes as quickly as possible, protecting your own hands and body. Place the victim under a deluge shower. If the chemical got on the victim's exposed skin, such as the hands: Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation: Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention. Ingestion:

Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Serious Ingestion: Not available.

#### **Section 5: Fire and Explosion Data**

Flammability of the Product: Non-flammable. Auto-Ignition Temperature: Not applicable.

Flash Points: Not applicable.
Flammable Limits: Not applicable.
Products of Combustion: Not available.

2

### SHANGHAI HUATING CHEMICALS FACTORY CO.,LTD

Fire Hazards in Presence of Various Substances: Not applicable.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions: Not applicable.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

#### Section 6: Accidental Release Measures

Small Spill: Use appropriate tools to put the spilled solid in a convenient waste disposal container. Large Spill:

Corrosive solid. Stop leak if without risk. Do not get water inside container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

#### Section 7: Handling and Storage

Precautions:

Keep locked up Keep container dry. Do not ingest. Do not breathe dust. Avoid contact with eyes Never add water to this product Wear suitable protective clothing In case of insufficient ventilation, wear suitable respiratory equipment If ingested, seek medical advice immediately and show the container or the label. Storage: Corrosive materials should be stored in a separate safety storage cabinet or room.

#### **Section 8: Exposure Controls/Personal Protection**

#### **Engineering Controls:**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection:

Splash goggles. Lab coat. Vapor and dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor and dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: TWA: 1 CEIL: 2 (mg/m3)Consult local authorities for acceptable exposure limits.

#### **Section 9: Physical and Chemical Properties**

Physical state and appearance: Solid. (Crystalline solid.)

Odor: Not available.

3

### SHANGHAI HUATING CHEMICALS FACTORY CO.,LTD

Taste: Not available.

Molecular Weight: 99 g/mole

Color: White.

pH (1% soln/water): Not available. Boiling Point: 1490℃ (2714年) Melting Point: 430℃ (806年)

Critical Temperature: Not available. Specific Gravity: 4.14 (Water = 1) Vapor Pressure: Not applicable. Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available. Water/Oil Dist. Coeff.: Not available. Ionicity (in Water): Not available.

Dispersion Properties: See solubility in water, diethyl ether.

Solubility:

Soluble in diethyl ether. Very slightly soluble in cold water.

#### Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available. Conditions of Instability: Not available.

Incompatibility with various substances: Not available.

Corrosivity: Non-corrosive in presence of glass. Special Remarks on Reactivity: Not available. Special Remarks on Corrosivity: Not available.

Polymerization: No.

#### **Section 11: Toxicological Information**

Routes of Entry: Eye contact. Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 140 mg/kg [Rat].

Chronic Effects on Humans: The substance is toxic to kidneys, lungs, liver, mucous membranes.

Other Toxic Effects on Humans:

Very hazardous in case of ingestion. Hazardous in case of inhalation. Slightly hazardous in case of skin contact (irritant).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available. Special Remarks on other Toxic Effects on Humans: Not available.

#### **Section 12: Ecological Information**

### SHANGHAI HUATING CHEMICALS FACTORY CO.,LTD

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

#### **Section 13: Disposal Considerations**

Waste Disposal:

#### **Section 14: Transport Information**

DOT Classification: CLASS 6.1: Poisonous material.

Identification: : Toxic solid, inorganic, n.o.s. (Cuprous Chloride) : UN3288 PG: III

Special Provisions for Transport: Marine Pollutant

#### **Section 15: Other Regulatory Information**

Federal and State Regulations:

Pennsylvania RTK: Cuprous chloride Massachusetts RTK: Cuprous chloride TSCA 8(b) inventory: Cuprous chloride SARA

313 toxic chemical notification and release reporting: Cuprous chloride CERCLA: Hazardous substances.:

Cuprous chloride

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:

WHMIS (Canada): CLASS E: Corrosive solid.

DSCL (EEC):

R25- Toxic if swallowed. R36- Irritating to eyes.

HMIS (U.S.A.): Health Hazard: 3 Fire Hazard: 0 Reactivity: 0

Personal Protection: j

National Fire Protection Association (U.S.A.):

Health: 3
Flammability: 0
Reactivity: 0
Specific hazard:

Protective Equipment:

Gloves. Lab coat. Vapor and dust respirator. Be sure to use an approved/certified respirator or equivalent.

5

# SHANGHAI HUATING CHEMICALS FACTORY CO.,LTD

Wear appropriate

respirator when ventilation is inadequate. Splash goggles.

#### **Section 16: Other Information**

References: Not available.

Other Special Considerations: Not available.

Created: 10/09/2005 05:01 PM

Last Updated: 11/06/2009 12:00 AM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Shanghai Huating Chemicals Factory Co.,Ltd be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Shanghai Huating Chemicals Factory Co.,Ltd has been advised of the possibility of such damages.